



VA46-H20整结构参数  
 整机尺寸： 1053.5\*608\*63  
 挂架孔间距： 600\*400  
 单位：mm

Dimension	>0-3	>3-6	>6-10	>10-18	>18-25	>25-40	>40-63	>63-100	>100-160	>160-250	>250-400	>400-630	>630-1000	
tolerance	±0.2	±0.24	±0.26	±0.27	±0.29	±0.32	±0.35	±0.39	±0.44	±0.50	±0.55	±0.60	±0.70	
unless	DIE CASTING Ref.QC T 269-1999													
otherwise	>0-1													
stated	>1-3													
for	>3-10													
metal	>10-30													
part	>30-120													
part	>120-315													
	>315-1000													
SHEET	Blanking, cutting, outline													
METAL	±0.025 ±0.035 ±0.05 ±0.07 ±0.10 ±0.14 ±0.20													
Ref.	Piercing, holes, and space between them. ±0.02 ±0.025 ±0.035 ±0.05 ±0.07 ±0.10 ±0.13													
SJ-11062	Distance from piercing/holes to edge. ±0.035 ±0.05 ±0.07 ±0.10 ±0.14 ±0.20 ±0.28													
-1995	Drawing, forming, extrusion. ±0.035 ±0.05 ±0.07 ±0.10 ±0.14 ±0.20 ±0.28													
Part Name:	Model Name:													
Part Number:	Designer:													
	Project:													
<b>TCL</b> Mechanical Department												Check:	Material:	Scale: 1:1
												Approve:	Weight:	Sheet: